



MADE IN SPAIN
Design by PRILUX



Applications



Industry/Logistics



Covered car parks
















Large surfaces

Certifications




Specifications (Series luminaires)

| | | |
|--|-----------------------------------|------------|
|  | Voltage (V) | 220-240V |
| Hz | Frecuency (Hz) | 50-60Hz |
|  | Current (A) | 500mA |
| ϕ | Power factor (Cos fi) | 0.98 |
|  | LED number | 360 |
|  | Dimming | No |
|  | IP Tightness index | IP66 |
|  | IK Impact resistance | IK10 |
|  | Body color | Light grey |
|  | Diffuser Material | PC-O |
|  | Body | PC |
| K | Colour temperature | 5.000K |
|  | CRI Colour rendering index | >80 |






| | | |
|---|------------------------------|----------------|
|  | Measures | 1.565x82x87mm |
|  | Weight | 2.7Kg |
|  | Mounting | Superficie |
|  | Operating temperature | -20°C |
| ϕ_{LUM} | Flux (lm) | 12.428lm |
|  | Electrical isolation | CCI |
|  | Lifetime | L90B10>200000h |

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions



References

| | | | | | | | | | | |
|---|-----------|-------|---|--------------|--------------|----------|---|--------|---|---|
|  | W_{LED} | W |  | ϕ_{LED} | ϕ_{LUM} | ϕ/W |  | K |  |  |
| 525251 | 2x41 | 85,2W | 500mA | 15.064lm | 12.428lm | 146lm/W | 360 | 5.000K | >80 | 1.565x82x87mm |

On request



Dali

K

>80 4.000K



Cableado Pasante



Presence and brightness sensor (mod.
1x/2x 1.200mm/1.500mm)



+45°C