


MADE IN SPAIN
Design by PRILUX



Applications



Industry/Logistics



Covered car parks

















Large surfaces

Certifications




Specifications (Series luminaires)

	Voltage (V)	220-240V
Hz	Frecuency (Hz)	50-60Hz
	Current (A)	650mA
ϕ	Power factor (Cos fi)	0.98
	LED number	360
	Dimming	No
	IP Tightness index	IP66
	IK Impact resistance	IK10
	Body color	Light grey
	Diffuser Material	PC-O
	Body	PC
K	Colour temperature	5.000K
	CRI Colour rendering index	>80






	Measures	1.565x82x87mm
	Weight	2.7Kg
	Mounting	Superficie
	Operating temperature	-20°C
ϕ_{LUM}	Flux (lm)	15.951lm
	Electrical isolation	CCI
	Lifetime	L90B10>200000h

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions



References

	W_{LED}	W		ϕ_{LED}	ϕ_{LUM}	ϕ/W		K		
525268	2x53	114,3W	650mA	19.217lm	15.951lm	140lm/W	360	5.000K	>80	1.565x82x87 mm

On request



Dali

K

>80 4.000K



Cableado Pasante



Presence and brightness sensor (mod.
1x/2x 1.200mm/1.500mm)