





**MADE IN SPAIN**  
Design by PRILUX




---

## Applications

---



Offices



Classrooms



Retail



Large surfaces



Hotels




















Restaurants



Health care


## Specifications (Series luminaires)

	<b>Voltage (V)</b>	220-240V
Hz	<b>Frecuency (Hz)</b>	50-60Hz
	<b>Current (A)</b>	300mA
$\phi$	<b>Power factor (Cos fi)</b>	0.97
	<b>LED number</b>	112
	<b>Dimming</b>	No
	<b>IP Tightness index</b>	IP20
	<b>IK Impact resistance</b>	IK04
	<b>Diffuser Material</b>	PC metalizado por altovacio
	<b>Body</b>	FE
	<b>Reflector</b>	AL-BR
K	<b>Colour temperature</b>	4.000K
	<b>CRI Colour rendering index</b>	>80
	<b>UGR</b>	UGR <19




	<b>Measures</b>	595x595x40mm
	<b>Weight</b>	5.7Kg
	<b>Mounting position</b>	Empotrar
	<b>Operating temperature</b>	+35°C
$\phi_{LUM}$	<b>Flux (lm)</b>	3.879lm
	<b>Electrical isolation</b>	CI
	<b>Lifetime</b>	L80B10>150.000h L90B10>74.000h

Prilux guarantees a  $\pm 10\%$  tolerance in light flux measurements.


## Dimensions



## References

	$W_{LED}$	W		$\phi_{LED}$	$\phi_{LUM}$	K	
526340	24W	26W	300mA	4.345lm	3.879lm	4.000K	595x595x40mm

**Photometry**



**On request**



Bluetooth



Available RAL colors (Consult)

**K**

>80 3.000K

>80 4.000K

>80 4.000K

Others (consult)



AL-MT (matt aluminium)

DO-MT (Matt gold)

CO-MT (Copper matt)

NE-MT (Matt black)

**Solutions**

S



**CTE Pack**

**description**



Regulation for the contribution of natural light to comply with the requirements of the CTE. Independent control of two lines of dimmable DALI luminaires with sensor to install in a luminaire or surface box. Preconfigured for easy operation.



**Was Indoor**

**description**



The WAS INDOOR solution is specifically aimed at increasing the well-being of users in places such as hospitals, nursing homes, wellness centres, classrooms and offices. The circadian lighting is applied in workplaces to improve visual conditions, comfort and the workers' performance, resulting in a higher productivity and a better development of the company.



**Bluetooth package**

**description**



Casambi version of our fixtures that enables through any Bluetooth® terminal via free APP that offers the control of flow regulation, color, scene configuration, behavior linked to schedules. Multiple accessories can be configured to work on the same network to unify the control of one or more spaces, being able to create groups, scenes and dynamic sequences to measure. The Bluetooth® device is valid for any DALI luminaire.

**Info**



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web [www.prilux.es](http://www.prilux.es)

**Info**



Led module