



Specifications (Series luminaires)							
	Electrical isolation	CII					
4	Voltage (V)	180-250V					
Hz	Frecuency (Hz)	50-60Hz					
\bigcirc	Dimming	1-10V					
L 0 0 0	IP Tightness index	IP20					
0	Body color	White					
14	Diffuser Material	PC-O					
<u> </u>	Body	AL					
Κ	Colour temperature	4.000K					
Ŕ	CRI Colour rendering index	>80					
A	Opening angle	120°					
${\longleftrightarrow}$	Measures	125x30mm					
\	Mounting position	Empotrar					
J ^{tc}	Operating temperature	-5°C~+35 °C					
$\varphi_{_{\text{LUM}}}$	Flux (lm)	635lm					
	Lifetime	(L70B50>) 50.000h					






References	5							
	W	$\varphi_{_{\text{LUM}}}$	К	Ŕ	Ŵ		${\longleftrightarrow}$	\bigcirc
532174	6W	635lm	4.000K	>80	White	100-110	125x30mm	Yes

Dimensions

 $\stackrel{}{\longleftrightarrow}$

Photometry

 \bigotimes







 $\langle 0 \rangle$

On request



Emergency kit 2hBajo el campo de configuración se añade solo este texto, en los 4 idiomas definidos

Accessories



532211

DRIVER KENTAU 6W 1-10V





Technologies



CELLTECH

CELLTECH technology is a revolutionary feeding system for luminaires that allow the extraction and exchange of drivers that facilitates

Ø

and simplifies the installation and mounting of luminaires. CELLTECH drivers are available without regulation and with 1-10V regulation and C-TOUCH.

4





S

Ø

(i)

Solutions



description

Regulation for the contribution of natural light to comply with the requirements of the CTE. Independent control of two lines of dimmable DALI luminaires with sensor to install in a luminaire or surface box. Preconfigured for easy operation.



CLASSROOMS Pack

description

Ø

Ø

Regulation by contribution of natural light and stand alone presence. Lighting control system to meet CTE requirements and optimize energy use by taking advantage of natural light and automatic shutdown in case of absence.



description

Device that enables DALI luminaire control through any Bluetooth® terminal via free APP that offers us control of flow regulation, color, scene configuration, behavior linked to schedules.

Info

For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es

5