



## Specifications (Series luminaires)

|                                                                                   |                              |          |
|-----------------------------------------------------------------------------------|------------------------------|----------|
|  | <b>Electrical isolation</b>  | CII      |
|  | <b>Voltage (V)</b>           | 100-240V |
| <b>Hz</b>                                                                         | <b>Frecuency (Hz)</b>        | 50-60Hz  |
|  | <b>Power factor (Cos fi)</b> | ≥0,5     |
|  | <b>Dimming</b>               | No       |

|                                                                                   |                           |      |
|-----------------------------------------------------------------------------------|---------------------------|------|
|  | <b>IP Tightness index</b> | IP20 |
|  | <b>Body color</b>         | 9006 |
|  | <b>Diffuser Material</b>  | PC-T |
|  | <b>Body</b>               | AL   |

|                                                                                     |                                   |        |
|-------------------------------------------------------------------------------------|-----------------------------------|--------|
| <b>K</b>                                                                            | <b>Colour temperature</b>         | 4.000K |
|  | <b>CRI Colour rendering index</b> | ≥80    |
|  | <b>Opening angle</b>              | 35°    |

|                                                                                     |                          |                 |
|-------------------------------------------------------------------------------------|--------------------------|-----------------|
|  | <b>Measures</b>          | Ø90x44mm        |
|  | <b>Mounting position</b> | Empotrado Techo |
|  | <b>Inclination</b>       | 25°             |


|                                                                                     |                              |        |
|-------------------------------------------------------------------------------------|------------------------------|--------|
|  | <b>Operating temperature</b> | -5 +35 |
|-------------------------------------------------------------------------------------|------------------------------|--------|

|                                                                                     |                  |       |
|-------------------------------------------------------------------------------------|------------------|-------|
|  | <b>Flux (lm)</b> | 573lm |
|-------------------------------------------------------------------------------------|------------------|-------|

|                                                                                     |                 |                  |
|-------------------------------------------------------------------------------------|-----------------|------------------|
|  | <b>Lifetime</b> | (L70B50>)15.000h |
|-------------------------------------------------------------------------------------|-----------------|------------------|

| References                                                                        |      |              |        |                                                                                   |                                                                                   |                                                                                     |                                                                                     |                                                                                     |  |
|-----------------------------------------------------------------------------------|------|--------------|--------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  | W    | $\phi_{LUM}$ | K      |  |  |  |  |  |                                                                                     |
| 545518                                                                            | 6,5W | 573lm        | 4.000K | ≥80                                                                               | Grey 9006                                                                         | Ø74                                                                                 | Ø90x44mm                                                                            | No                                                                                  |                                                                                     |

Dimensions



Photometry