




---

## Applications

---















Covered car parks



Large surfaces


## Specifications (Series luminaires)

 <b>Voltage (V)</b>	220-240V
<b>Hz</b> <b>Frecuency (Hz)</b>	50-60Hz
 <b>Current (A)</b>	300mA
$\phi$ <b>Power factor (Cos fi)</b>	0.96
 <b>LED number</b>	96
 <b>Dimming</b>	No
 <b>IP Tightness index</b>	IP65
 <b>IK Impact resistance</b>	IK08
 <b>Body color</b>	Light grey
 <b>Diffuser Material</b>	PC-O
 <b>Body</b>	PC
<b>K</b> <b>Colour temperature</b>	5.000K
 <b>CRI Colour rendering index</b>	>80






 <b>Measures</b>	2x-1.270x125x88mm
 <b>Weight</b>	2.6Kg
 <b>Operating temperature</b>	-20~+35°C
$\phi_{LUM}$ <b>Flux (lm)</b>	5.554lm
 <b>Electrical isolation</b>	CI
 <b>Lifetime</b>	L70B10>50.000h

Prilux guarantees a  $\pm 10\%$  tolerance in light flux measurements.


## Dimensions



## References

	$W_{LED}$	$W$		$\phi_{LED}$	$\phi_{LUM}$		<b>K</b>		
<b>550628</b>	2 x 22	46W	300mA	6.300lm	5.554lm	96	5.000K	>80	2x-1.270x125x88mm

## Photometry



## On request



Emergency kit 3h (mod. 1x/2x  
1.200mm/1.500mm)



Presence and brightness sensor (mod.  
1x/2x 1.200mm/1.500mm)



Regulation 1-10V

Dali

K

>80 4.000K

---

## Accessories

---



---

### 378376

---

SET OF 8 PLASTIC  
CLIPS BERLIN ECO  
T8 1200MM

## Technologies



# Overstorm

### Overstorm



OVERSTORM technology is designed for those luminaires that normally face electrically aggressive environments. It provides the product with three spheres of protection: In the outer sphere, an independent surge protector suppresses eventual voltage surges, in the intermediate sphere the drivers are prepared to withstand voltage peaks of up to 6 kV and 10kV. In the nuclear sphere, the protection in the LED module is provided both at its input, for small surges that have not been filtered by the external spheres.

### Warning



You need DALI drive

## Solutions

S



### Cora Industry

#### description



The CORA device in its three versions; INDUSTRY UNIT, INDUSTRY and CORA INDUSTRY MASTER controls the lighting of new or even existing installations thanks to wireless technology such as BLUETOOTH 5.0

#### Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web [www.prilux.es](http://www.prilux.es)