







Applications





Covered car parks

Large surfaces



Specifications (Series luminaires)

4	Voltage (V)	220-240V
Hz	Frecuency (Hz)	50-60Hz
Ð	Current (A)	300mA
φ	Power factor (Cos fi)	0.97
-)	LED number	120
\bigcirc	Dimming	No

\bigcirc	Dimming	No	$\varphi_{_{\text{LUM}}}$
	IP Tightness index	IP65	
` ↓	IK Impact resistance	IK08	
\odot	Body color	Light grey	
14	Diffuser Material	PC-O	
Ì!	Body	PC	
		·	


К	Colour temperature	4.000K
Ŕ	CRI Colour rendering index	>80

${\longleftrightarrow}$	Measures	2x-1.570x125x88mm			
O kg	Weight 2.6Kg				
fl ^{tc}	Operating temperature	-20~+35°C			
$\varphi_{_{\text{LUM}}}$	Flux (lm)	6.450lm			
	Electrical isolation	CI			
	Lifetime	L70B10>50.000h			

Prilux guarantees a ± 10% tolerance in light flux measurements.

Dimensions

 $\stackrel{}\longleftrightarrow$



References									
	W	W		$\varphi_{_{\text{LED}}}$	$\varphi_{_{\text{LUM}}}$	-``_	K	Ø	\longleftrightarrow
550703	2 x 28	57W	300mA	7.500lm	6.450lm	120	4.000K	>80	2x-1.570x125x 88mm

Berlin Avant



On request





Presence and brightness sensor (mod. 1x/2x 1.200mm/1.500mm)

\bigcirc	
Regulation 1-10V	
Dali	



Accessories



5



378406

SET OF 10 PLASTIC CLIPS BERLIN ECO T8 1500MM





Technologies



Overstorm

OVERSTORM technology is designed for those luminaires that normally face electrically aggressive environments. It provides the product with three spheres of protection: In the outer sphere, an independent surge protector suppresses eventual voltage surges, in the intermediate sphere the drivers are prepared to withstand voltage peaks of up to 6 kV and 10kV. In the nuclear sphere, the protection in the LED module is provided both at its input, for small surges that have not been filtered by the external spheres.

Ø

Warning

You need DALI drive

Berlin Avant



S

(i)

Solutions



description

The CORA device in its three versions; INDUSTRY UNIT, INDUSTRY and CORA INDUSTRY MASTER controls the lighting of new or even existing installations thanks to wireless technology such as BLUETOOTH 5.0

Info

Ø

For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es