




Applications







Covered car parks





Large surfaces

Specifications (Series luminaires)









 Voltage (V)	220-240V
Hz Frecuency (Hz)	50-60Hz
 Current (A)	300mA
ϕ Power factor (Cos fi)	0.93
 LED number	48
 Dimming	No


 Measures	1x-1.270x85x88mm
 Weight	2.6Kg

 Operating temperature	-20~+35°C
--	-----------

ϕ_{LUM} Flux (lm)	2.640lm
-------------------------------	---------

 IP Tightness index	IP65
 IK Impact resistance	IK08
 Body color	Light grey
 Diffuser Material	PC-O
 Body	PC


 Electrical isolation	CI
---	----

 Lifetime	L70B10>50.000h
---	----------------

K Colour temperature	4.000K
 CRI Colour rendering index	>80

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions



References



	W_{LED}	W		ϕ_{LED}	ϕ_{LUM}		K		
550765	1 x 22	24W	300mA	3.000lm	2.640lm	48	4.000K	>80	1x-1.270x85x88mm

On request



Emergency kit 3h (mod. 1x/2x
1.200mm/1.500mm)



Presence and brightness sensor (mod.
1x/2x 1.200mm/1.500mm)



Regulation 1-10V

Dali

K

>80 4.000K

Accessories



378376

SET OF 8 PLASTIC
CLIPS BERLIN ECO
T8 1200MM

Technologies



Overstorm

Overstorm



OVERSTORM technology is designed for those luminaires that normally face electrically aggressive environments. It provides the product with three spheres of protection: In the outer sphere, an independent surge protector suppresses eventual voltage surges, in the intermediate sphere the drivers are prepared to withstand voltage peaks of up to 6 kV and 10kV. In the nuclear sphere, the protection in the LED module is provided both at its input, for small surges that have not been filtered by the external spheres.

Warning



You need DALI drive

Solutions

S



Cora Industry

description



The CORA device in its three versions; INDUSTRY UNIT, INDUSTRY and CORA INDUSTRY MASTER controls the lighting of new or even existing installations thanks to wireless technology such as BLUETOOTH 5.0

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es