




---

## Applications

---


















Covered car parks



Large surfaces


## Specifications (Series luminaires)

	<b>Voltage (V)</b>	220-240V
Hz	<b>Frecuency (Hz)</b>	50-60Hz
	<b>Current (A)</b>	350mA
$\phi$	<b>Power factor (Cos fi)</b>	0.95
	<b>LED number</b>	48
	<b>Dimming</b>	No
	<b>IP Tightness index</b>	IP65
	<b>IK Impact resistance</b>	IK08
	<b>Body color</b>	Light grey
	<b>Diffuser Material</b>	PC-O
	<b>Body</b>	PC
K	<b>Colour temperature</b>	3.000K
	<b>CRI Colour rendering index</b>	>80




	<b>Measures</b>	1x-1.270x85x88mm
	<b>Weight</b>	2.6Kg
	<b>Operating temperature</b>	-20~+35°C
$\phi_{LUM}$	<b>Flux (lm)</b>	2.888lm
	<b>Electrical isolation</b>	CI
	<b>Lifetime</b>	L70B10>50.000h

Prilux guarantees a  $\pm 10\%$  tolerance in light flux measurements.

## Dimensions



## References

	$W_{LED}$	W		$\phi_{LED}$	$\phi_{LUM}$		K		
<b>550789</b>	1 x 26	28W	350mA	3.282lm	2.888lm	48	3.000K	>80	1x-1.270x85x88mm

## On request



Emergency kit 3h (mod. 1x/2x  
1.200mm/1.500mm)



Presence and brightness sensor (mod.  
1x/2x 1.200mm/1.500mm)



Regulation 1-10V

Dali

K

>80 4.000K

## Accessories



**378376**

SET OF 8 PLASTIC  
CLIPS BERLIN ECO  
T8 1200MM

## Technologies



# Overstorm

### Overstorm



OVERSTORM technology is designed for those luminaires that normally face electrically aggressive environments. It provides the product with three spheres of protection: In the outer sphere, an independent surge protector suppresses eventual voltage surges, in the intermediate sphere the drivers are prepared to withstand voltage peaks of up to 6 kV and 10kV. In the nuclear sphere, the protection in the LED module is provided both at its input, for small surges that have not been filtered by the external spheres.

### Warning



You need DALI drive

---

## Solutions

---

S



### Cora Industry

---

#### description



The CORA device in its three versions; INDUSTRY UNIT, INDUSTRY and CORA INDUSTRY MASTER controls the lighting of new or even existing installations thanks to wireless technology such as BLUETOOTH 5.0

---

#### Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web [www.prilux.es](http://www.prilux.es)