



### **Applications**







Covered car parks


Large surfaces



Spe	ecifications (Series lumin	aires)			=
4	Voltage (V)	220-240V	$\longrightarrow$	Measures	1x-1.570x85x88mm
Hz	Frecuency (Hz)	50-60Hz	O /kg	Weight	2.6Kg
	Current (A)	300mA			
φ	Power factor (Cos fi)	0.95	- Atc	Operating temperature	-20~+35°C
<u>`</u>	LED number	60			·
$\bigcirc$	Dimming	No	$\Phi_{\text{\tiny LUM}}$	Flux (lm)	3.387lm
00	IP Tightness index	IP65		Electrical isolation	CI
L L	IK Impact resistance	IK08			·
$\odot$	Body color	Light grey		Lifetime	L70B10>50.000h
11/	Diffuser Material	PC-O			·
	Body	PC			
K	Colour temperature	5.000K			
Ø	CRI Colour rendering index	>80			

### **Dimensions**





References														
	V <sub>LED</sub>	W	Ţ	ф	ф <sub>ьим</sub>	-)	K	Ø	$\longleftrightarrow$					
550864	1 x 28	30W	300mA	3.938lm	3.387lm	60	5.000K	>80	1x-1.570x85x8 8mm					



#### On request





Emergency kit 3h (mod. 1x/2x 1.200mm/1.500mm)



Presence and brightness sensor (mod. 1x/2x 1.200mm/1.500mm)



Regulation 1-10V

Dali



>80 4.000K

#### **Accessories**





#### 378406

SET OF 10 PLASTIC CLIPS BERLIN ECO T8 1500MM



Technologies E



#### **Overstorm**



OVERSTORM technology is designed for those luminaires that normally face electrically aggressive environments. It provides the product with three spheres of protection: In the outer sphere, an independent surge protector suppresses eventual voltage surges, in the intermediate sphere the drivers are prepared to withstand voltage peaks of up to 6 kV and 10kV. In the nuclear sphere, the protection in the LED module is provided both at its input, for small surges that have not been filtered by the external spheres.

### Warning



You need DALI drive



Solutions S



#### description



The CORA device in its three versions; INDUSTRY UNIT, INDUSTRY and CORA INDUSTRY MASTER controls the lighting of new or even existing installations thanks to wireless technology such as BLUETOOTH 5.0

#### Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es