



Applications




















Covered car parks




Large surfaces

Specifications (Series luminaires)











 Voltage (V)	220-240V	 Measures	1x-1.570x85x88mm
Hz Frequency (Hz)	50-60Hz	 Weight	2.6Kg
 Current (A)	390mA	 Operating temperature	-20~+35°C
ϕ Power factor (Cos fi)	0.96	 Flux (lm)	3.973lm
 LED number	60	 Electrical isolation	CI
 Dimming	No	 Lifetime	L70B10>50.000h
 IP Tightness index	IP65	 IK Impact resistance	IK08
 Body color	Light grey	 Diffuser Material	PC-O
 Body	PC	 Colour temperature	3.000K
 CRI Colour rendering index	>80		

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions



References

									
550901	1 x 37	39W	390mA	4.619lm	3.973lm	60	3.000K	>80	1x-1.570x85x8 8mm

On request



Emergency kit 3h (mod. 1x/2x
1.200mm/1.500mm)



Presence and brightness sensor (mod.
1x/2x 1.200mm/1.500mm)



Regulation 1-10V

Dali

K

>80 4.000K

Accessories



378406

SET OF 10 PLASTIC
CLIPS BERLIN ECO
T8 1500MM

Technologies



Overstorm

Overstorm



OVERSTORM technology is designed for those luminaires that normally face electrically aggressive environments. It provides the product with three spheres of protection: In the outer sphere, an independent surge protector suppresses eventual voltage surges, in the intermediate sphere the drivers are prepared to withstand voltage peaks of up to 6 kV and 10kV. In the nuclear sphere, the protection in the LED module is provided both at its input, for small surges that have not been filtered by the external spheres.

Warning



You need DALI drive

Solutions

S



Cora Industry

description



The CORA device in its three versions; INDUSTRY UNIT, INDUSTRY and CORA INDUSTRY MASTER controls the lighting of new or even existing installations thanks to wireless technology such as BLUETOOTH 5.0

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es