



Applications







Covered car parks

Large surfaces




Prilux guarantees a ± 10% tolerance in light flux measurements.

Spe	cifications (Series lumin	aires)		=				
4	Voltage (V)	220-240V	←	Measures	1x-1.570x85x88mm			
Hz	Frecuency (Hz)	50-60Hz		Weight	2.6Kg			
	Current (A)	390mA			·			
φ	Power factor (Cos fi)	0.96	- Atc	Operating temperature	-20~+35°C			
<u> </u>	LED number	60			·			
\bigcirc	Dimming	No	ф	Flux (lm)	4.346lm			
		,						
0 0	IP Tightness index	IP65		Electrical isolation	CI			
L L	IK Impact resistance	IK08			·			
00	Body color	Light grey		Lifetime	L70B10>50.000h			
14	Diffuser Material	PC-O			·			
	Body	PC						
K	Colour temperature	5.000K						
Ø	CRI Colour rendering index	>80						

Dimensions





References														
	V LED	W		ф _{LED}	ф	-\	K	∀	\longleftrightarrow					
550925	1 x 37	39W	390mA	5.053lm	4.346lm	60	5.000K	>80	1x-1.570x85x8 8mm					



On request





Emergency kit 3h (mod. 1x/2x 1.200mm/1.500mm)



Presence and brightness sensor (mod. 1x/2x 1.200mm/1.500mm)



Regulation 1-10V

Dali



>80 4.000K

Accessories





378406

SET OF 10 PLASTIC CLIPS BERLIN ECO T8 1500MM



Technologies E



Overstorm



OVERSTORM technology is designed for those luminaires that normally face electrically aggressive environments. It provides the product with three spheres of protection: In the outer sphere, an independent surge protector suppresses eventual voltage surges, in the intermediate sphere the drivers are prepared to withstand voltage peaks of up to 6 kV and 10kV. In the nuclear sphere, the protection in the LED module is provided both at its input, for small surges that have not been filtered by the external spheres.

Warning



You need DALI drive



Solutions S



description



The CORA device in its three versions; INDUSTRY UNIT, INDUSTRY and CORA INDUSTRY MASTER controls the lighting of new or even existing installations thanks to wireless technology such as BLUETOOTH 5.0

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es