Tanek Arq Rgbw







Applications





Monuments



Fairgrounds



Facades



Historic buildings



Cultural spaces

Tanek Arq Rgbw



pecifications (Series I	uminaires)		=======================================
$\frac{1}{2}$ Voltage (V)	V	—— ← Measures	0mm
Z Frecuency (Hz)	Hz		
Dimming	No	Surges protection	No
		Prilux guarantees a ± 10% tolerance	in light flux measurements.
		Prilux guarantees a ± 10% tolerance	in light flux measurements.
		Prilux guarantees a ± 10% tolerance	in light flux measurements.
•		Prilux guarantees a ± 10% tolerance	
imensions		Prilux guarantees a ± 10% tolerance	in light flux measurements.
imensions		Prilux guarantees a ± 10% tolerance	←
imensions		Prilux guarantees a ± 10% tolerance	←
imensions		Prilux guarantees a ± 10% tolerance	←
imensions		Prilux guarantees a ± 10% tolerance	←
imensions		Prilux guarantees a ± 10% tolerance	
imensions		Prilux guarantees a ± 10% tolerance	
imensions		Prilux guarantees a ± 10% tolerance	
imensions		Prilux guarantees a ± 10% tolerance	
imensions		Prilux guarantees a ± 10% tolerance	
imensions		Prilux guarantees a ± 10% tolerance	←

Tanek Arq Rgbw



Info

î

The RSSY remote installation systems are indivisibly composed of HEXAGON RSSY floodlights connected to a POWER BOX(not included in theluminaire). The POWER BOX must be purchased separately. Check with your local sales representative for the best combination a dapted to your installation.