



## Applications



Home




Hotels




Restaurants



Retail



Offices



Classrooms











Retrofit



Under furniture


## Specifications (Series luminaires)

	<b>Electrical isolation</b>	CCIII
	<b>Voltage (V)</b>	24V
	<b>IP Tightness index</b>	IP20
<b>K</b>	<b>Colour temperature</b>	6500K
	<b>CRI Colour rendering index</b>	80cromatica




	<b>Measures</b>	5.000x10mm
	<b>Mounting position</b>	Superficie
	<b>Lifetime</b>	(L70B50>)50.000h
	<b>Lifetime</b>	(L70B50>)50.000h

Prilux guarantees a  $\pm 10\%$  tolerance in light flux measurements.

## Dimensions



## References

	<b>W</b>	<b>K</b>		
<b>568487</b>	4,8W	6500K	80cromatica	5.000x10mm

---

## Rules

---



Pérdida de intensidad para más de 10m (4,8W/m-9,6W/m-14,4W/m).

La vida útil de nuestras tiras de led es de 50.000h siempre que la temperatura ambiente no supere los 25°C.

Con el fin de garantizar la vida del led para nuestras tiras  $\geq$  9,6W, es obligatorio colocarlo sobre una superficie que disipe

**Ima 24v Ip20 4.8w**  
568487

PRILUX 