











Specifications (Series luminaires)


	Electrical isolation	CIII
	Voltage (V)	24V dcV
Hz	Frecuency (Hz)	50-60Hz
	IP Tightness index	IP20
K	Colour temperature	4.000K
	CRI Colour rendering index	>90
	Opening angle	120°
	Measures	5.000x10mm
	Strip cutting unit	50mm
	Lifetime	(L70B50>) 50.000h

References



	W	K			
568609	14,4W	4.000K	>90	50mm	5.000x10mm

Dimensions



Photometry




Accessories




472395

IMAGINE
MONOCOLOR RF
REGULATOR 5-24V
1X5A




242813

POWER SUPPLY
60W 24VDC LED
STRIP



242820

POWER SUPPLY
150W 24VDC LED
STRIP



242837

POWER SUPPLY
250W 24VDC LED
STRIP



473682

POWER SUPPLY
60W 24V IP67
LPV-60-24



473699

POWER SUPPLY
100W 24V IP67
LPV-100-24



473705

POWER SUPPLY
150W 24V IP67
LPV-150-24




473057

CONNECTOR
IMAGINE
MONOCOLOR IP20
CABLE-STRIP



473071

CONNECTOR
IMAGINE
MONOCOLOR IP20
STRIP-STRIP



209151

STRIP CONNECTOR X
IP20 2835 10MM 2P



209144

T-STRIP CONNECTOR
IP20 2835 10MM 2P



501453

POWER SUPPLY
XLG-200-24-A IP67

Accessories



001662

POWER SUPPLY
DALI LCA 35W 24V
SC PRE



001663

POWER SUPPLY
DALI LCA 60W 24V
SC PRE



001253

POWER SUPPLY
DALI LCA 100W 24V
SC PRE



001437

POWER SUPPLY
DALI LCA 150W 24V
SC PRE



487863

POWER SUPPLY BT
HLC 35 / 24V bDW SC
PRE2



487870

POWER SUPPLY BT
LC 60 / 24V bDW SC
PRE2



487887

POWER SUPPLY BT
LC 100 / 24V bDW SC
PRE2



487894

POWER SUPPLY BT
LC 150 / 24V bDW SC
PRE2