Imagine lp20





Specifications (Series luminaires)						
opc	Cirications (Scries idiniii	<u> </u>				
	Electrical isolation	CIII				
4	Voltage (V)	24V dcV				
Hz	Frecuency (Hz)	50-60Hz				
00	IP Tightness index	IP20				
K	Colour temperature	2.700K~6.500K				
Ø	CRI Colour rendering index	>90				
A	Opening angle	120°				
↔ *	Measures	2.000x10mm				
%	Strip cutting unit	50mm				
	Lifetime	(L70B50>) 50.000h				

Imagine lp20



References					
	W	K	À	%	← ↑
568708	19,2W	2.700K~6.500K	>90	50mm	2.000x10mm

Dimensions



Photometry





Info



>5m less performance ((19,2W/m - 19,2W/m WAS - 24,5W/m). The life time of our LED strips is 50.000h as long as the ambient temperature does not exceed 25°C. To ensure the life of the LED for our strips \geq 9.6W, it is mandatory to place it on a surface that dissipates the heat they generate.

Imagine lp20




Accessories









472401

IMAGINE DUAL RF REGULATOR 5-24V 2X5A



IMAGINE DUAL AMPLIFIER 5-24V 2X5A



POWER SUPPLY 60W 24VDC LED STRIP 242820

POWER SUPPLY 150W 24VDC LED STRIP









242837

POWER SUPPLY 250W 24VDC LED STRIP 473682

POWER SUPPLY 60W 24V IP67 LPV-60-24 473699

POWER SUPPLY 100W 24V IP67 LPV-100-24 473705

POWER SUPPLY 150W 24V IP67 LPV-150-24



501453

POWER SUPPLY XLG-200-24-A IP67