



MADE IN SPAIN
Design by PRILUX



Applications



Roads



Motorways



Parks



Viaducts




Pedestrian Zones



Cycle lanes



Car parks



Industrial






















Residential Areas

Certifications




Specifications (Series luminaires)

| | | |
|--|-----------------------------------|-----------|
|  | Voltage (V) | 220-240V |
| Hz | Frecuency (Hz) | 50-60Hz |
|  | Current (A) | 700mA |
| ϕ | Power factor (Cos fi) | 0.97 |
|  | LED number | 12 |
|  | Dimming | 8N - DALI |
|  | Comm. Prot. for reprogr. | CMR |
|  | IP Tightness index | IP66 |
|  | IK Impact resistance | IK08 |
|  | Body color | 9007 |
|  | Diffuser Material | VT-T 5mm |
|  | Body | AL iap |
| K | Colour temperature | 3.000K |
|  | CRI Colour rendering index | >70 |
|  | Optical | VA00K0M |




| | | |
|--|------------------------------|-------------------|
|  | Measures | 525x255x105mm |
|  | Weight | 5Kg |
|  | Wind Resistance | 0,151m2 |
|  | Mounting | Crosier Mount |
|  | Operating temperature | -40~+50°C |
| ϕ_{LUM} | Flux (lm) | 3382lm |
|  | Electrical isolation | CI |
|  | Lifetime | L90 B10 >200.000h |
| ϕ/W | Efficacy | 128lm/W |

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.


Dimensions



References


| | | | | | | | | | |
|---|-----------|-------|---|--------|--------------|--------------|----------|---|----------|
|  | W_{LED} | W |  | ϕ | ϕ_{LED} | ϕ_{LUM} | ϕ/W |  | K |
| 568913 | 24W | 26,5W | 700mA | 4239lm | 3933lm | 3382lm | 128lm/W | 12 | 3.000K |

Photometry




On request






Dali

Double Level with Line of Command



Class II



PC-T (IK10)

K

PCAmbar


>70 2.700K

>80 3.000K

>80 4.000K

PC Amber Filter

>70 2.700K



Available RAL colors (Consult)

50 °C (Consult available powers and optics)



PPDL0M

PPILOM

S150L0M

VA00I0P

VA00L0M

VA01L0M

VA02L0M

VA03D0P

VA04D0P

VA05I0P

VA06I0P



VA07L0P

PPILOM

PPILOM

Light packages



| | | | PCA | 722 | 727 | 730 | 827 | 830 | 840 |
|--------------|---|---|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| W |  |  | ϕ_{LUM} ϕ/W | ϕ_{LUM} ϕ/W | ϕ_{LUM} ϕ/W | ϕ_{LUM} ϕ/W | ϕ_{LUM} ϕ/W | ϕ_{LUM} ϕ/W | ϕ_{LUM} ϕ/W |
| 26,5W | 12 | 700mA | 1.781lm 67lm/W | 2.716lm 102lm/W | 3.198lm 121lm/W | 3.383lm 128lm/W | 2.892lm 109lm/W | 2.892lm 109lm/W | 3.048lm 115lm/W |

Mounting



1. Crosier Mount

Accessories



534222

KIT ADAP. TO POST
50MM AVATAR

538282

KIT ADAP. A POSTE
Ø42MM AVATAR

479776

KIT ADAP. A POSTE
Ø33MM AVATAR

501743

KIT ADAP. A POSTE
Ø76MM
POLIVALENTE TECN.
RAL9007T



Technologies



Overstorm



OVERSTORM technology is designed for those luminaires that normally face electrically aggressive environments. It provides the product with three spheres of protection: In the outer sphere, an independent surge protector suppresses eventual voltage surges, in the intermediate sphere the drivers are prepared to withstand voltage peaks of up to 6 kV and 10kV. In the nuclear sphere, the protection in the LED module is provided both at its input, for small surges that have not been filtered by the external spheres.

SystemShield



SYSTEMSHIELD technology is designed to guarantee the hours of useful life of luminaires installed in environments where exceeding the maximum operating temperature is possible and even probable. Using thermal probes, the luminaire knows its operating temperature at all times.



CMR



CMR (CORA MANAGER READY) identifies the prilux luminaires compatible with the CORA MANAGER system that provides the luminaires with control, regulation and programming.

WAS



WAS (White Adaptive System) technology provides PRILUX luminaires with the ability to change both the amount of light they provide and the correlated color temperature, CCT.

Rules



Complies with IDAE and CEI requirements; and with R.D. 1890/2008 (Regulation on energy efficiency of outdoor lighting).

Solutions

S



**Was
Outdoor**

description



WAS (White Adaptive System) technology provides PRILUX luminaires with the ability to change both the amount of light they provide and the correlated color temperature, CCT. WAS (White Adaptive System) technology provides PRILUX luminaires with the ability to change both the amount of light they provide and the correlated color temperature



**Cora
Manager**

description



One of the key pieces to achieve the path towards smart cities is lighting. Lighting management systems are advancing by leaps and bounds, prioritizing primary objectives such as service quality, cost reduction and care for the environment. CORA Manager is the control system developed by Prilux that, together with our compatible luminaires that provides intelligent management of public lighting, maintaining harmony between sustainable development and quality of life for citizens, while promoting safety and saving.



Safelight

description



SAFELIGHT allows the lighting of zebra crossings with road luminaires adapted with special optics for this application that illuminate with white light with a continuous level of 100%

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es