













Specifications (Series luminaires)




	Electrical isolation	CIII
	Voltage (V)	24V dcV
	Frecuency (Hz)	50-60Hz
	IP Tightness index	IP65
	Colour temperature	2.700K
	CRI Colour rendering index	>80
	Opening angle	120°
	Measures	5.000x10mm
	Strip cutting unit	50mm
	Lifetime	(L70B50>) 50.000h

References



	W	K			
569033	14,4W	2.700K	>80	50mm	5.000x10mm

Dimensions



Photometry



Info



Loss of intensity for more than 10m. The useful life of our led strips is 50,000h as long as the temperature ambient temperature does not exceed 25 ° C. Mandatory placement of strips on surfaces that dissipate heat that they generate in order to guarantee the life of the led,

Accessories



472395

IMAGINE
MONOCOLOR RF
REGULATOR 5-24V
1X5A



473682

POWER SUPPLY
60W 24V IP67
LPV-60-24



473699

POWER SUPPLY
100W 24V IP67
LPV-100-24



473705

POWER SUPPLY
150W 24V IP67
LPV-150-24




473040

CONNECTOR
IMAGINE
MONOCOLOR IP65
CABLE-STRIP




473064

CONNECTOR
IMAGINE
MONOCOLOR IP65
STRIP-STRIP



209151

STRIP CONNECTOR X
IP20 2835 10MM 2P



209144

T-STRIP CONNECTOR
IP20 2835 10MM 2P



501453

POWER SUPPLY
XLG-200-24-A IP67



001662

POWER SUPPLY
DALI LCA 35W 24V
SC PRE



001663

POWER SUPPLY
DALI LCA 60W 24V
SC PRE



001253

POWER SUPPLY
DALI LCA 100W 24V
SC PRE

Accessories



001437

POWER SUPPLY
DALI LCA 150W 24V
SC PRE



487863

POWER SUPPLY BT
HLC 35 / 24V bDW SC
PRE2



487870

POWER SUPPLY BT
LC 60 / 24V bDW SC
PRE2



487887

POWER SUPPLY BT
LC 100 / 24V bDW SC
PRE2



487894

POWER SUPPLY BT
LC 150 / 24V bDW SC
PRE2