



MADE IN SPAIN
Design by PRILUX



Applications



Parks



Residential Areas



Pedestrian Zones



Cycle lanes















Car parks








Certifications






Specifications (Series luminaires)

	Voltage (V)	220-240V
Hz	Frecuency (Hz)	50-60Hz
	Current (A)	700mA
ϕ	Power factor (Cos fi)	0.97
	LED number	12
	Dimming	8N - DALI
	Comm. Prot. for reprogr.	CMR
	IP Tightness index	IP65
	IK Impact resistance	IK08
	Diffuser Material	PC-P
	Body	AL iap
K	Colour temperature	3.000K
	CRI Colour rendering index	>70
	Optical	VA00LIM
	Higher Hemispheric Flow	10%lm




	Measures	Ø500x580mm
	Weight	12.5Kg
	Wind Resistance	0,196m2
	Mounting	Arm Mount
	Operating temperature	-40~+35°C
ϕ_{LUM}	Flux (lm)	2.344lm
	Electrical isolation	CI
	Lifetime	L90 B10 >200.000h
ϕ/W	Efficacy	88lm/W

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.


Dimensions



References

	W_{LED}	W		ϕ	ϕ_{LED}	ϕ_{LUM}	ϕ/W		K
569781	24W	26,5W	700mA	4.239lm	3.973lm	2.344lm	88lm/W	12	3.000K

Photometry



On request



Dali

Double Level with Line of Command

K

PCAmbar

>70 2.700K

>80 3.000K



>80 4.000K




Available RAL colors (Consult)

Light packages



			PCA	722	727	730	827	830	840
W			ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W
26,5W	12	700mA	1.242lm 47lm/W	1.894lm 71lm/W	2.235lm 84lm/W	2.344lm 88lm/W	2.017lm 76lm/W	2.017lm 76lm/W	2.126lm 80lm/W

Mounting



1. Arm Mount

Accessories



587105

KIT ADAP. A POSTE
Ø33MM GAUDIUM-
LIVIA-SFERA

587112

KIT ADAP. A POSTE
Ø42MM GAUDIUM-
LIVIA-SFERA

587129

KIT ADAP. A POSTE
Ø50MM GAUDIUM-
LIVIA-SFERA

587143

KIT ADAP. A POSTE
Ø76MM
POLIVALENTE DECO.
RAL9005T

Technologies



Overstorm



OVERSTORM technology is designed for those luminaires that normally face electrically aggressive environments. It provides the product with three spheres of protection: In the outer sphere, an independent surge protector suppresses eventual voltage surges, in the intermediate sphere the drivers are prepared to withstand voltage peaks of up to 6 kV and 10kV. In the nuclear sphere, the protection in the LED module is provided both at its input, for small surges that have not been filtered by the external spheres.

SystemShield



SYSTEMSHIELD technology is designed to guarantee the hours of useful life of luminaires installed in environments where exceeding the maximum operating temperature is possible and even probable. Using thermal probes, the luminaire knows its operating temperature at all times.



CMR



CMR (CORA MANAGER READY) identifies the prilux luminaires compatible with the CORA MANAGER system that provides the luminaires with control, regulation and programming.



Cora Manager

description



One of the key pieces to achieve the path towards smart cities is lighting. Lighting management systems are advancing by leaps and bounds, prioritizing primary objectives such as service quality, cost reduction and care for the environment. CORA Manager is the control system developed by Prilux that, together with our compatible luminaires that provides intelligent management of public lighting, maintaining harmony between sustainable development and quality of life for citizens, while promoting safety and saving.

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es

Info



Includes Optical Group with ENAC tests and ENEC, CB, N certification