



Specifications (Series luminaires)					
	Electrical isolation	CII			
4	Voltage (V)	230V			
Hz	Frecuency (Hz)	50-60Hz			
$\bigcirc$	Dimming	No			
00	IP Tightness index	IP20			
00	IP installed Sealing rating	44			
00	Body color	White			
11/	Diffuser Material	PS			
	Body	FE			
K	Colour temperature	4.000K			
Ø	CRI Colour rendering index	>80			
Д	Opening angle	120°			
$\longleftrightarrow$	Measures	595x595x20mm			
<b>←</b>	Mounting position	Empotrar			
ф	Flux (lm)	4.156lm			
	Lifetime	(L70B50>) 30.000h			







References									
	₩ <sub>LED</sub>	W		ф	Ф	K		$\bigcirc$	
582070	36W	32W	1000mA	5.305lm	4.156lm	4.000K	575 x 575	No	

Dimensions	_1
	`.

Photometry







## Etna Basic 582070



### On request









Dan

Bluetooth

### **Accessories**





### 964562

FRAME WH RECESSED PLASTER SILENT LED 60X60CM



### 164092

WH SURFACE DRAWER SILENT LED 60X60CM



### 397391

RECESSED CEILING FRAME HIDDEN PROFILE SILENT I 60X60

## Etna Basic



Solutions S



### CTE Pack

# CLASSROOMS Pack

### description



Regulation for the contribution of natural light to comply with the requirements of the CTE. Independent control of two lines of dimmable DALI luminaires with sensor to install in a luminaire or surface box. Preconfigured for easy operation.

### description



Regulation by contribution of natural light and stand alone presence. Lighting control system to meet CTE requirements and optimize energy use by taking advantage of natural light and automatic shutdown in case of absence.

### Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es