





## **Applications**





Monuments



**Fairgrounds** 



Facades



Historic buildings




Cultural spaces



Spe	cifications (Series lumin	aires)			:
4	Voltage (V)	220-240V	$\longleftrightarrow$	Measures	489x118x180mm
Ηz	Frecuency (Hz)	50-60Hz			
	Current (A)	700mA	$\Box$	Surges protection	No
φ	Power factor (Cos fi)	0.98			
<u> </u>	LED number	40	ф	Flux (lm)	5.554lm
$\bigcirc$	Dimming	No			
		,		Electrical isolation	CI
00	IP Tightness index	IP66			
L	IK Impact resistance	IK10	<u></u>	Lifetime	L90B10>184.000h
D	Body color	9007			
11/	Diffuser Material	PC-T	-		
	Body	AL iap	-		
			-		
K	Colour temperature	RGBW(W:4000K)	-		
Ø	CRI Colour rendering index	>80 (Blanco)	-		
; ; ; ;	Optical	PEXLOM	Prilux	guarantees a ± 10% tolerance	in light flux measurements

## **Dimensions**






eference	S							
	\$0	<b>V</b> V		ф <sub>LED</sub>	ф	-\	<del>까</del>	$\bigcirc$
586399	ARQ 1X	82 máx.	700mA	6.653lm	5.554lm	40	HERRO40-	No



## **Photometry**





## On request





深
AEXLOM
AINLOM
PINLOM
S014L0M
S025L0M
S074L0M
S137L0M
S154L0M



Accessories



#### 452311

ACCES. MOBILE FINS 1X120LED HEXAGON



#### 452335

ACCESORIO VISERA 1X120LED HEXAGON



#### 452670

KIT CONEXION HEXAGON REMOTO RGBW 3MTS



#### 452687

KIT CONEXION HEXAGON REMOTO RGBW 5MTS



#### 471428

KIT CONEXION HEXAGON REMOTO RGBW 7MTS



#### 471596

KIT CONEXION HEXAGON REMOTO RGBW 10MTS



Solutions S



### description



CORA SPORTS is the family of devices by Priluxto control DALI light fixtures in new or existing installations, indoors or outdoors, using Bluetooth5.0 wireless technology. Technology that is more efficient and easierto deploy and scale for professional lighting applications. It can work in a meshedarrangement with the light fixtures and to createsmart communication networks. Especially recommended in installations with towers and/or groups of light fixtures to make it possible tooperate them as a group or individually.

#### Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es



Info	j
You need DALI drive	