



---

## Applications

---



Fairgrounds



Facades


















Historic buildings



Cultural spaces


## Specifications (Series luminaires)

 <b>Voltage (V)</b>	220-240V
<b>Hz</b> <b>Frecuency (Hz)</b>	50-60Hz
 <b>LED number</b>	18
 <b>Dimming</b>	No
 <b>IP Tightness index</b>	IP66
 <b>IK Impact resistance</b>	IK09
 <b>Body color</b>	9007
 <b>Diffuser Material</b>	VT
 <b>Body</b>	AL
<b>K</b> <b>Colour temperature</b>	4000k
 <b>CRI Colour rendering index</b>	>80




 <b>Measures</b>	960x102x88mm
 <b>Operating temperature</b>	-20°C a +35°C
 <b>Surges protection</b>	No
 <b>Flux (lm)</b>	3.485lm
 <b>Electrical isolation</b>	CI
 <b>Lifetime</b>	L70B10> 100.000h

Prilux guarantees a  $\pm 10\%$  tolerance in light flux measurements.

## Dimensions



## References

	$W_{LED}$	<b>W</b>	$\phi_{LED}$	$\phi_{LUM}$		
<b>591829</b>	42W	45W	4.017lm	3.485lm	18	No

## Photometry

