

MADE IN SPAIN
Design by PRILUX



Applications




Facades



Industrial




Car parks



Sports grounds



Monuments



Industrial Zones

Certifications



Specifications (Series luminaires)

	Voltage (V)	220-240V
Hz	Frecuency (Hz)	50/60Hz
	Current (A)	350mA
ϕ	Power factor (Cos fi)	0.93
	LED number	108
	Dimming	No
	IP Tightness index	IP66
	IK Impact resistance	IK09
	Body color	9007
	Body	AL iap
K	Colour temperature	4000K
	CRI Colour rendering index	>70
	Optical	VA1112P

	Measures	250x55x438mm
	Weight	0.007Kg
	Wind Resistance	0,11m2
	Operating temperature	-30°C ~ +50°C
	Surges protection	No
	Flux (lm)	5,976lm
	Electrical isolation	CI
	Lifetime	L70B10> 100.000h
	Lifetime	L70B10> 100.000h

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions

References

				ϕ	ϕ_{LED}	ϕ_{LUM}	ϕ/W			
592284	35W	38W	350mA	7874lm	7761lm	5976lm	157lm/W	108	VA1112P	No

Light packages



			PCA	722	727	730	827	830	840
W			ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W
38W	108	350mA					4.695lm 124lm/W	4.909lm 129lm/W	5.335lm 140lm/W

Accessories



515788

ACCESSORY
PARALUMEN
NANTES RAL9005T

Solutions

S



Cora Manager

description



Lighting management in the electrical panel that allows group control of the luminaires connected to the control center via the power line (CMR) without additional wiring

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es