


MADE IN SPAIN
Design by PRILUX



Applications




Facades



Industrial



Car parks



Sports grounds



Monuments











Industrial Zones



Certifications






Specifications (Series luminaires)

	Voltage (V)	220-240V
Hz	Frecuency (Hz)	50-60Hz
	Current (A)	475mA
	LED number	36
	Dimming	Yes


	IP Tightness index	IP66
	IK Impact resistance	IK09
	Body color	RAL9007
	Body	AL iap


K	Colour temperature	RGBW
	CRI Colour rendering index	RGBW
	Optical	PEXL0M


	Measures	500x250x55mm
	Weight	5.75Kg
	Wind Resistance	0,11m2

	Operating temperature	-30°C + 50°C
---	------------------------------	--------------

	Surges protection	No
---	--------------------------	----


	Flux (lm)	4097lm
---	------------------	--------

	Electrical isolation	CCI
---	-----------------------------	-----











	Lifetime	L70B10>100.000h
---	-----------------	-----------------

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions





References

									
609302	46W	54,5W	475mA	-lm	4710lm	4097lm	36	PEXL0M	Yes

On request



	
Dali	VA00I0P
Bluetooth	AEXL0M
	AINL0M
	VA12I2P
	S011L0M
	S0135L0M
	S024L0M
	S071L0M
	S151L0M

Accessories



515788

ACCESSORY

PARALUMEN

NANTES RAL9005T