




MADE IN SPAIN
Design by PRILUX



Applications




Facades



Industrial



Car parks



Sports grounds



Monuments



Industrial Zones

Certifications



Specifications (Series luminaires)

	Voltage (V)	220-240V
	Frecuency (Hz)	50-60Hz
	Current (A)	700mA
	Power factor (Cos fi)	0.97
	LED number	108
	Dimming	No
	IP Tightness index	IP66
	IK Impact resistance	IK09
	Body color	9007
	Body	AL iap
	Colour temperature	3000K
	CRI Colour rendering index	70cromatica
	Optical	VA1112P

	Measures	500x250x55mm
	Wind Resistance	0,11m2
	Operating temperature	50°C
	Surges protection	No
	Flux (lm)	10782lm
	Electrical isolation	CCI
	Lifetime	L70B10>100.000h
	Lifetime	L70B10> 100.000h

Prilux guarantees a ± 10% tolerance in light flux measurements.

Dimensions

References

										
621137	73W	79,1W	700mA	14160lm	14002lm	10782lm	136lm/W	108	VA1112P	No

Light packages

			PCA	722	727	730	827	830	840
W			ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W
79,1W	108	700mA					8.785lm 111lm/W	9.184lm 116lm/W	9.983lm 126lm/W

Accessories



515788

ACCESSORY
PARALUMEN
NANTES RAL9005T

Solutions

S



Cora
Manager

description

Lighting management in the electrical panel that allows group control of the luminaires connected to the control center via the power line (CMR) without additional wiring

Info 

For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es