



Applications





Monuments



Fairgrounds



Facades



Historic buildings



Cultural spaces

Tanek Arq



Specifications (Series	luminaires)		=
$ \sqrt[A]{} $ Voltage (V)	V	——— ← Measures	0mm
Dimming	No	- Measures	- On the second
	110	Surges protection	No
		Our ges protession	110
		Prilux guarantees a ± 10% tolerance	in light flux measurements.
		Prilux guarantees a ± 10% tolerance	in light flux measurements.
		Prilux guarantees a ± 10% tolerance	in light flux measurements.
Dimonsions.		Prilux guarantees a ± 10% tolerance	
Dimensions		Prilux guarantees a ± 10% tolerance	
Dimensions		Prilux guarantees a ± 10% tolerance	←
Dimensions		Prilux guarantees a ± 10% tolerance	←
Dimensions		Prilux guarantees a ± 10% tolerance	←
Dimensions		Prilux guarantees a ± 10% tolerance	←
Pimensions		Prilux guarantees a ± 10% tolerance	←
Dimensions		Prilux guarantees a ± 10% tolerance	←
Dimensions		Prilux guarantees a ± 10% tolerance	←
Dimensions		Prilux guarantees a ± 10% tolerance	←
		Prilux guarantees a ± 10% tolerance	←
		Prilux guarantees a ± 10% tolerance	←
References		Prilux guarantees a ± 10% tolerance	←

Tanek Arq



Info

j

The RSSY remote installation systems are indivisibly composed of HEXAGON RSSY floodlights connected to a POWER BOX(not included in theluminaire). The POWER BOX must be purchased separately. Check with your local sales representative for the best combination a dapted to your installation.