

















### Specifications (Series luminaires)



	<b>Voltage (V)</b>	220-240V
<b>Hz</b>	<b>Frecuency (Hz)</b>	50-60Hz
	<b>Power factor (Cos fi)</b>	>0,9
	<b>Dimming</b>	No
	<b>IP Tightness index</b>	IP20
	<b>IP installed Sealing rating</b>	44
	<b>Body color</b>	White
	<b>Diffuser Material</b>	PC-O
	<b>Body</b>	PC
<b>K</b>	<b>Colour temperature</b>	4.000K
	<b>CRI Colour rendering index</b>	>80
	<b>Opening angle</b>	120°
	<b>Measures</b>	225x225x50mm
	<b>Flux (lm)</b>	2400lm
	<b>Electrical isolation</b>	CII
	<b>Lifetime</b>	(L70B50>) 50.000h



### References




	W	$\phi_{LUM}$	K					
<b>628952</b>	20W	2400lm	4.000K	>80	White	205 x 205	225x225x50m	No

### Dimensions



### Photometry



## On request




Emergency kit 2hBajo el campo de configuración se añade solo este texto, en los 4 idiomas definidos



Dali

## Accessories



**629249**

ACCESORIO SUPERFICIE KENTAU AVANT SQ 20W BLANCO



**600828**

DRIVER KENTAU AVANT 12-20W DALI DT6 PUSH

---

## Solutions

---

S



### BLUETOOTH Pack

---

#### description

---

Device that enables DALI luminaire control through any Bluetooth® terminal via free APP that offers us control of flow regulation, color, scene configuration, behavior linked to schedules.

---

---

#### Info

---

For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web [www.prilux.es](http://www.prilux.es)