




Specifications (Series luminaires)

	Electrical isolation	CCI
	Voltage (V)	100-240V
Hz	Frecuency (Hz)	50-60HzHz
	Power factor (Cos fi)	0.9
	Dimming	1-10V
	IP Tightness index	IP65
	IK Impact resistance	IK10
	Body color	Black
	Diffuser Material	PC
	Body	AL
K	Colour temperature	4.000K/5.000K
	CRI Colour rendering index	>80
	Measures	Ø240x165mm
	Operating temperature	(-30°C,+50 °C)
	Flux (lm)	8400/11200/14000lm
	Lifetime	>50.000h

References

	W_{LED}	W		ϕ_{LED}	ϕ_{LUM}	Δ	K		
629690	92W	100W	600mA	8652/11536/14 120lm	8400/11200/1 4000lm	90°	4.000K/5.000 K	>80	Ø240x165m m

Dimensions



Photometry



Info



With power selector and CCT via switch

Accessories



507578

REMOTE CONTROL
HIGH HEIGHT
MOTION DETECTOR



629911

LIRA AKORA 100W
185X130X52MM



629782

REFLECTOR AKORA
ALUMINIO 100W 60°



629812

REFLECTOR AKORA
ALUMINIO 100W 90°



629881

REJILLA
PROTECTORA
AKORA 100W