





ecifications (Series luminaires)						
Electrical isolation	CI					
Voltage (V)	100-240V					
Z Frecuency (Hz)	50/60Hz					
Power factor (Cos fi)	0.9					
Dimming	No					
O IP Tightness index	IP65					
IK Impact resistance	IK10					
Diffuser Material	PC					
Body	AL					
	,					
Colour temperature	5000K					
CRI Colour rendering	index >80					
Ò Measures	0x0x165mm					
Operating temperatu	-30°C ~ +50°C					
Flux (lm)	16,500lm					
Lifetime	L70>50000h					






Reference	S							
	W		ф _{ьер}	ф _{ьим}	A	K	₩	←
629720	100W	600mA	16995lm	16500lm	90°	5000K	80	0x0x165mm
						5000K		

Dimensions ←

Photometry









Accessories









629911

AKORA LYRA 100W 185X130X52MM 629782

REFLECTOR AKORA ALUMINIO 100W 60° 629812

REFLECTOR AKORA ALUMINIO 100W 90° UGR 629881

REJILLA PROTECTORA AKORA 100W





Solutions S



Cora Industry

BLUETOOTH Pack

description



The CORA device in its three versions; INDUSTRY UNIT, INDUSTRY and CORA INDUSTRY MASTER controls the lighting of new or even existing installations thanks to wireless technology such as BLUETOOTH 5.0

description



Device that enables DALI luminaire control through any Bluetooth® terminal via free APP that offers us control of flow regulation, color, scene configuration, behavior linked to schedules.

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es