






е	ecifications (Series luminaires)					
)	Electrical isolation	CI				
	Voltage (V)	100-240V				
Z	Frecuency (Hz)	50/60Hz				
)	Power factor (Cos fi)	0.9				
)	Dimming	No				
0	IP Tightness index	IP65				
L	IK Impact resistance	IK10				
″/	Diffuser Material	PC				
	Body	AL				
<	Colour temperature	4000K				
Ä	CRI Colour rendering index	>80				
\Rightarrow	Measures	0x0x165mm				
} ^{tc}	Operating temperature	-30°C ~ +50°C				
) LUM	Flux (lm)	16,500lm				
	Lifetime	L70>50000h				





Reference	s							
	W		ф _{ьер}	ф _{ьим}	A	K	\\	\longleftrightarrow
629737	100W	600mA	16995lm	16500lm	90°	4000K 4000K	80	0x0x165mm









Accessories









629911

AKORA LYRA 100W 185X130X52MM 629782

REFLECTOR AKORA ALUMINIO 100W 60° 629812

REFLECTOR AKORA ALUMINIO 100W 90° UGR 629881

REJILLA PROTECTORA AKORA 100W





Solutions S



BLUETOOTH Pack

description



The CORA device in its three versions; INDUSTRY UNIT, INDUSTRY and CORA INDUSTRY MASTER controls the lighting of new or even existing installations thanks to wireless technology such as BLUETOOTH 5.0

description



Device that enables DALI luminaire control through any Bluetooth® terminal via free APP that offers us control of flow regulation, color, scene configuration, behavior linked to schedules.

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es