





| pecifications (Series luminaires) | | | | | | |
|-----------------------------------|---------------|--|--|--|--|--|
| Electrical isolation | CI | | | | | |
| Voltage (V) | 100-240V | | | | | |
| Z Frecuency (Hz) | 50/60Hz | | | | | |
| Power factor (Cos fi) | 0.9 | | | | | |
| Dimming | No | | | | | |
| | • | | | | | |
| D IP Tightness index | IP65 | | | | | |
| > IK Impact resistance | IK10 | | | | | |
| Diffuser Material | PC | | | | | |
| Body | AL | | | | | |
| | | | | | | |
| Colour temperature | 5000K | | | | | |
| CRI Colour rendering in | >80 | | | | | |
| | | | | | | |
| → Measures | 0x0x165mm | | | | | |
| | | | | | | |
| Operating temperature | -30°C ~ +50°C | | | | | |
| | | | | | | |
| Flux (lm) | 24,750lm | | | | | |
| | | | | | | |
| Lifetime | L70>50000h | | | | | |






| Reference | S | | | | | | | |
|-----------|------|-------|------------------|------------------|-----|-------|----|-----------------------|
| | W | | ф _{ьер} | ф _{ьим} | A | K | Ÿ | \longleftrightarrow |
| 629744 | 150W | 750mA | 25493lm | 24750lm | 90° | 5000K | 80 | 0x0x165mm |
| | | | | | | 5000K | | |

Dimensions

Photometry









Accessories







629799

REFLECTOR AKORA ALUMINIO 150W 60° 629898

REJILLA PROTECTORA AKORA 150W 629928

LIRA AKORA 150W 222X130X52MM





Solutions S



Industry

description

The CORA device in its three versions; INDUSTRY UNIT, INDUSTRY and CORA INDUSTRY MASTER controls the lighting of new or even existing installations thanks to wireless technology such as BLUETOOTH 5.0



description



Device that enables DALI luminaire control through any Bluetooth® terminal via free APP that offers us control of flow regulation, color, scene configuration, behavior linked to schedules.

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es