










Specifications (Series luminaires)			☰
⚡	Electrical isolation	CI	
⚡	Voltage (V)	100-240V	
Hz	Frecuency (Hz)	50/60Hz	
φ	Power factor (Cos fi)	0.9	
○	Dimming	No	
⚡	IP Tightness index	IP65	
⚡	IK Impact resistance	IK10	
▢	Diffuser Material	PC	
⚡	Body	AL	
K	Colour temperature	4000K	
🌱	CRI Colour rendering index	>80	
↕	Measures	0x0x165mm	
🌡️	Operating temperature	-30°C ~ +50°C	
φ _{LUM}	Flux (lm)	24,750lm	
⌛	Lifetime	L70>50000h	

References								
	W		ϕ_{LED}	ϕ_{LUM}		K		
629751	150W	750mA	25493lm	24750lm	90°	4000K 4000K	80	0x0x165mm

Dimensions	Photometry
	

Accessories



629799

REFLECTOR AKORA
ALUMINIO 150W 60°

629898

REJILLA
PROTECTORA
AKORA 150W

629928

LIRA AKORA 150W
222X130X52MM

Solutions S



Cora Industry

description 

The CORA device in its three versions; INDUSTRY UNIT, INDUSTRY and CORA INDUSTRY MASTER controls the lighting of new or even existing installations thanks to wireless technology such as BLUETOOTH 5.0



BLUETOOTH Pack

description 

Device that enables DALI luminaire control through any Bluetooth® terminal via free APP that offers us control of flow regulation, color, scene configuration, behavior linked to schedules.

Info 

For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es