

















Specifications (Series luminaires)

| | | |
|---|-----------------------------------|------------|
|  | Electrical isolation | CCI |
|  | Voltage (V) | 100-240V |
| Hz | Frecuency (Hz) | 50-60Hz |
|  | Power factor (Cos fi) | 0.9 |
|  | Dimming | No |
|  | IP Tightness index | IP65 |
|  | IK Impact resistance | IK10 |
|  | Body color | RAL9005 |
|  | Diffuser Material | PC |
|  | Body | AL |
| K | Colour temperature | 5000K |
|  | CRI Colour rendering index | >80 |
|  | Measures | Ø320x165mm |
|  | Operating temperature | 50°C |
|  | Flux (lm) | 33000lm |
|  | Lifetime | L70>50000h |

References




|  | W |  | ϕ_{LUM} | Δ | K |  |  |
|---|------|---|--------------|----------|-------|---|---|
| 629768 | 200W | 1000mA | 33000lm | 90° | 5000K | >80 | Ø320x165mm |


Dimensions



Photometry



Accessories



629836

REFLECTOR AKORA
ALUMINIO 200W 90°

629904

REJILLA
PROTECTORA
AKORA 200W

629935

LIRA AKORA 200W
264X130X52MM



Solutions

S



Cora Industry

description



The CORA device in its three versions; INDUSTRY UNIT, INDUSTRY and CORA INDUSTRY MASTER controls the lighting of new or even existing installations thanks to wireless technology such as BLUETOOTH 5.0



BLUETOOTH Pack

description



Device that enables DALI luminaire control through any Bluetooth® terminal via free APP that offers us control of flow regulation, color, scene configuration, behavior linked to schedules.

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es