




Specifications (Series luminaires)

	Voltage (V)	220-240V
Hz	Frecuency (Hz)	50/60Hz
	Current (A)	500mA
ϕ	Power factor (Cos fi)	0.94
	LED number	12
	Dimming	8N DA CMR
K	Colour temperature	4000K
	CRI Colour rendering index	>70
	Optical	VA00LIP
	Higher Hemispheric Flow	0,0%
	Measures	408x408x175mm
	Weight	0,004Kg
	Operating temperature	-40°C ~ +50°C
ϕ_{LUM}	Flux (lm)	2,627lm
	Electrical isolation	CI
	Lifetime	L90B10>200.000H L95B10>100.000H
ϕ/W	Efficacy	140lm/W

References										
	W_{LED}	W		ϕ	ϕ_{LED}	ϕ_{LUM}	ϕ/W		K	
634823	18W	18,8W	500mA	3310lm	2985lm	2627lm	140lm/W	12	4000K	

Dimensions		Photometry	
			

Solutions

S



Cora

Manager

description

Lighting management in the electrical panel that allows group control of the luminaires connected to the control center via the power line (CMR) without additional wiring

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es