




Specifications (Series luminaires)			
	Voltage (V)	220-240V	
Hz	Frecuency (Hz)	50/60Hz	
	Current (A)	700mA	
ϕ	Power factor (Cos fi)	0.97	
	LED number	12	
	Dimming	8N DA CMR	
K	Colour temperature	4000K	
	CRI Colour rendering index	>70	
	Optical	VA00LIP	
	Higher Hemispheric Flow	0,0%	
	Measures	408x408x175mm	
	Weight	0,004Kg	
	Operating temperature	-40°C ~ +50°C	
ϕ_{LUM}	Flux (lm)	3,516lm	
	Electrical isolation	CI	
	Lifetime	L90B10>200.000H L95B10>100.000H	
ϕ/W	Efficacy	133lm/W	

References										
	W_{LED}	W		ϕ	ϕ_{LED}	ϕ_{LUM}	ϕ/W		K	
634830	24W	26,5W	700mA	4437lm	3995lm	3516lm	133lm/W	12	4000K	

Dimensions		Photometry	
			

Solutions

S



Cora

Manager

description

Lighting management in the electrical panel that allows group control of the luminaires connected to the control center via the power line (CMR) without additional wiring

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es