





Applications



Classrooms



Health care



Offices



Large surfaces



Home



Hotels


















Restaurants




Retail

Specifications (Series luminaires)

 Voltage (V)	220-240V	 Measures	1.205x57x76mm
Hz Frecuency (Hz)	50/60Hz	 Weight	0.00212Kg
 Current (A)	500mA	 Mounting position	Surface Wall,Suspended
ϕ Power factor (Cos fi)	>0,9	 Operating temperature	-20°C ~ +45°C
 Dimming	No	ϕ_{LUM} Flux (lm)	3,350lm
 IP Tightness index	IP20	 Electrical isolation	CI
 IK Impact resistance	IK02	 Lifetime	L70>50000h
 Body color	9005	Colour temperature	3000K-4000K
 Diffuser Material	PC	 CRI Colour rendering index	>80
 Body	AL		

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions



References

	W		ϕ_{LUM}	\angle	K		
650366	32W	500mA	3350lm	100°	3000K 4000K	1.205x57x76mm	>80

On request



Emergency kit 3h (mod. 1x/2x
1.200mm/1.500mm)



Dali

Accessories



662895

ACCESORIO DE
SUSPENSION LYNX
PRO



662918

ACC. DE
SUSPENSION CON
ALIMENTACION LYNX





700269

ACCESORIO
CONEXION LINEAL
ADOSADO LYNX PRO



700276

ACCESORIO
CONEXION LINEAL
SUSPENSION LYNX




700290

ACCESORIOS
CONEXION L LYNX
PRO OPAL+PRISM



700313

ACCESORIO
CONEXION X LYNX
PRO OPAL+PRISM



700337

ACCESORIO
CONEXION T LYNX
PRO OPAL+PRISM



700443

ACCESORIO
ANCLAJE A PARED
LYNX PRO R9005T