



Specifications (Series luminaires)

|                                                                                   |                       |         |
|-----------------------------------------------------------------------------------|-----------------------|---------|
|  | Electrical isolation  | CI      |
|  | Voltage (V)           | 230V    |
|  | Frecuency (Hz)        | 50/60Hz |
|  | Power factor (Cos fi) | ≥0,9    |
|  | Dimming               | No      |

|                                                                                   |                      |        |
|-----------------------------------------------------------------------------------|----------------------|--------|
|  | IP Tightness index   | IP66   |
|  | IK Impact resistance | IK08   |
|  | Body color           | 9007   |
|  | Diffuser Material    | PC-T   |
|  | Body                 | AL iap |

|                                                                                     |                            |                   |
|-------------------------------------------------------------------------------------|----------------------------|-------------------|
|  | Colour temperature         | 3000K-4000K-5000K |
|  | CRI Colour rendering index | >70               |
|  | Optical                    | Simétrica         |

|                                                                                     |          |               |
|-------------------------------------------------------------------------------------|----------|---------------|
|  | Measures | 320x320x100mm |
|-------------------------------------------------------------------------------------|----------|---------------|

|                                                                                     |                       |               |
|-------------------------------------------------------------------------------------|-----------------------|---------------|
|  | Operating temperature | -20°C ~ +50°C |
|-------------------------------------------------------------------------------------|-----------------------|---------------|

|                                                                                     |           |             |
|-------------------------------------------------------------------------------------|-----------|-------------|
|  | Flux (lm) | max. 9100lm |
|-------------------------------------------------------------------------------------|-----------|-------------|

|                                                                                     |          |                |
|-------------------------------------------------------------------------------------|----------|----------------|
|  | Lifetime | L70B50> 50000h |
|-------------------------------------------------------------------------------------|----------|----------------|

References

|  | W   | $\phi_{LUM}$ | K     |
|-----------------------------------------------------------------------------------|-----|--------------|-------|
| 662383                                                                            | 30W | 3900lm       | 3000K |
|                                                                                   | 50W | 6500lm       | 4000K |
|                                                                                   | 70W | 9100lm       | 5000K |

Dimensions



Photometry

