



## Specifications (Series luminaires)

|                                                                                   |                              |             |
|-----------------------------------------------------------------------------------|------------------------------|-------------|
|  | <b>Electrical isolation</b>  | CI          |
|  | <b>Voltage (V)</b>           | 100-277VacV |
| <b>Hz</b>                                                                         | <b>Frecuency (Hz)</b>        | 50/60Hz     |
|  | <b>Power factor (Cos fi)</b> | >0,95       |
|  | <b>Dimming</b>               | DALI        |

|                                                                                   |                             |          |
|-----------------------------------------------------------------------------------|-----------------------------|----------|
|  | <b>IP Tightness index</b>   | IP66     |
|  | <b>IK Impact resistance</b> | IK09     |
|  | <b>Body color</b>           | 9007AS-T |
|  | <b>Diffuser Material</b>    | PC       |
|  | <b>Body</b>                 | AL iap   |

|                                                                                     |                                   |          |
|-------------------------------------------------------------------------------------|-----------------------------------|----------|
| <b>K</b>                                                                            | <b>Colour temperature</b>         | 4000K    |
|  | <b>CRI Colour rendering index</b> | >70      |
|  | <b>Optical</b>                    | PC S-030 |
|  | <b>Opening angle</b>              | 30°      |

|                                                                                     |                          |                 |
|-------------------------------------------------------------------------------------|--------------------------|-----------------|
|  | <b>Measures</b>          | 460x158x280mm   |
|  | <b>Mounting position</b> | Montaje en Lira |
|  | <b>Inclination</b>       | 180°            |

|                                                                                     |                              |               |
|-------------------------------------------------------------------------------------|------------------------------|---------------|
|  | <b>Operating temperature</b> | -40°C ~ +50°C |
|-------------------------------------------------------------------------------------|------------------------------|---------------|

|                                                                                     |                  |          |
|-------------------------------------------------------------------------------------|------------------|----------|
|  | <b>Flux (lm)</b> | 59,430lm |
|-------------------------------------------------------------------------------------|------------------|----------|

|                                                                                     |                 |                |
|-------------------------------------------------------------------------------------|-----------------|----------------|
|  | <b>Lifetime</b> | L90B10>100000h |
|-------------------------------------------------------------------------------------|-----------------|----------------|


References

|  | W    | $\phi_{LUM}$ | K     |  |  |
|-----------------------------------------------------------------------------------|------|--------------|-------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 679275                                                                            | 400W | 59430lm      | 4000K | Aluminio 9007                                                                       | 460x158x280mm                                                                       |

Dimensions



Photometry



On request



|                                                                                   |
|-----------------------------------------------------------------------------------|
|  |
| PC S-150                                                                          |
| PC S-150                                                                          |
| PC S-150                                                                          |