
















Specifications (Series luminaires)

	Electrical isolation	CII
	Voltage (V)	V
Hz	Frecuency (Hz)	50/60Hz
	Power factor (Cos fi)	>0,9
	Dimming	No


	IP Tightness index	IP20
	IP installed Sealing rating	IP44
	Body color	White
	Diffuser Material	PMMA-O
	Body	AL

K	Colour temperature	6500K
	CRI Colour rendering index	>80
	Opening angle	110°
	UGR	NO

	Measures	530x191x77mm
	Mounting position	Recessed Ceiling
	Cut dimensions	275 x 1175

	Operating temperature	-20°C ~ +40°C
---	------------------------------	---------------

	Flux (lm)	4,000lm
---	------------------	---------

	Lifetime	(L70B50>)50.000h
---	-----------------	------------------

References





	W_{LED}	W		ϕ	ϕ_{LUM}	K		
679640	36W	40W	1000mA	>0,9	4000lm	6500K	275 x 1175	No

Dimensions



Photometry






207591

FRAME BL RECESS
PLASTER SILENT LED
120X30CM



207874

WH SURFACE
DRAWER SILENT
LED 120X30CM



472500

SUSPENSION KIT
1.5M SILENT LED (4
UNITS)



484039

WH SURFACE
DRAWER SILENT
LED I 30X120X4,8CM