



Applications



Home




Hotels




Restaurants




Retail



Offices



Classrooms



Halls



Health care


Specifications (Series luminaires)

|                                                                                  |                            |                   |
|----------------------------------------------------------------------------------|----------------------------|-------------------|
|  | Voltage (V)                | 220-240V          |
| Hz                                                                               | Frecuency (Hz)             | 50-60Hz           |
| $\phi$                                                                           | Power factor (Cos fi)      | >0,9              |
|  | Dimming                    | No                |
|  | IP Tightness index         | IP20              |
|  | Body color                 | White             |
|  | Diffuser Material          | PC                |
| K                                                                                | Colour temperature         | 3000K-4000K-5700K |
|  | CRI Colour rendering index | >80               |

|                                                                                   |                       |                       |
|-----------------------------------------------------------------------------------|-----------------------|-----------------------|
|  | Measures              | 200x200x97mm          |
|  | Cut dimensions        | 165-180               |
|  | Mounting position     | Empotrado Techo       |
|  | Operating temperature | -20°C ~ +40°C         |
| $\phi_{LUM}$                                                                      | Flux (lm)             | 2,663, 2,683, 2,697lm |
|  | Electrical isolation  | CII                   |
|  | Lifetime              | L70>60.000h           |

Prilux guarantees a  $\pm 10\%$  tolerance in light flux measurements.

Dimensions



References

|                                                                                     |     |                    |          |                         |                                                                                       |                                                                                       |
|-------------------------------------------------------------------------------------|-----|--------------------|----------|-------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  | W   | $\phi_{LUM}$       | $\Delta$ | K                       |  |  |
| 684491                                                                              | 28W | 2663, 2683, 2697lm | 60°      | 3000K<br>4000K<br>5700K | 200x200x97mm                                                                          | >80                                                                                   |

On request





Dali

Bluetooth

Accessories





684651

ARO DECORATIVO  
NEGRO SEKOA  
SWITCH 28W 200MM