



Applications



Home




Hotels




Restaurants




Retail



Offices



Classrooms



Halls



Health care

Specifications (Series luminaires)

	Voltage (V)	220-240V
Hz	Frecuency (Hz)	50-60Hz
	Current (A)	900mA
ϕ	Power factor (Cos fi)	>0,9
	Dimming	No

	IP Tightness index	IP20
	Body color	White
	Diffuser Material	PC
	Body	AL

K	Colour temperature	3000K-4000K-5700K
	CRI Colour rendering index	>80

	Measures	232x232x110mm
	Cut dimensions	195-210
	Mounting position	Empotrado Techo

	Operating temperature	-20°C ~ +40°C
---	------------------------------	---------------


ϕ_{LUM}	Flux (lm)	max. 3363lm
--------------	------------------	-------------

	Electrical isolation	CII
---	-----------------------------	-----

	Lifetime	L70>60.000h
---	-----------------	-------------

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions



References

	W		ϕ_{LUM}	Δ	K		
684507	35W	900mA	3329lm 3349lm 3363lm	60°	3000K 4000K 5700K	232x232x110mm	>80

On request





Dali

Bluetooth

Accessories



684668

ARO DECORATIVO
NEGRO SEKOA
SWITCH 35W 232MM



684682

ACCESORIO
SUPERFICIE BLANCO
SEKOA SWITCH 35W



684705

ACCESORIO
SUPERFICIE NEGRO
SEKOA SWITCH 35W