




Applications



Historic buildings



Cultural spaces



















Facades




Fairgrounds

Specifications (Series luminaires)

| | | | |
|--|---------------|--|------------------|
|  Voltage (V) | 24 dcV |  Measures | 1.000x38x96mm |
|  Dimming | DMX |  Weight | 0.00202Kg |
|  IP Tightness index | IP66 |  Operating temperature | -30°C ~ +50°C |
|  IK Impact resistance | IK08 |  Surges protection | No |
|  Body color | 9007 |  Flux (lm) | 965lm |
|  Diffuser Material | PC |  Electrical isolation | CIII |
|  Body | AL |  Lifetime | (L70B50>)50.000h |
| K Colour temperature | RGBW(W:3000) | | |
|  CRI Colour rendering index | >RGBW(W:3000) | | |
|  Optical | - | | |

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions



References

| | | | | | | |
|---|-----|---|---|----------|---|---|
|  | W |  |  | ϕ/W |  |  |
| 693868 | 24W | -lm | 965lm | 40lm/W | - | Yes |



485135

MASTER DMX 512 1
UNIVERSE



481687

POWER SUPPLY
150W 24V IP66 PLUG/
IP44



488457

FUENTE DE
ALIMENTACION 60W
24V IP66 CONECTOR



488464

POWER SUPPLY
100W 24V IP66 PLUG/
IP44



529037

MASTER DMX 512 2
UNIVERSOS



571968

FUENTE DE
ALIMENTACION
200W 24V IP67



662932

ADAPT. 15CM NEGRO
CONEC.SMART LINK
A HEMBRA RÁPIDO



701600

BLOQUE CONEXION
T 5P CON
ADAPTADOR




705028

CONECTOR WC
AUTOBLOCANTE
MACHO/HEMBRA 2P




705042

CONECTOR WC
AUTOBLOCANTE
MACHO/HEMBRA 5P



708739

MG 60245 IEC57
(YZW) 2X1+3X0,3
CORTE 1 METRO



715249

MG-XTREM H07 RN-F
2X1 450/750V CORTE
1 METRO