




Applications



Historic buildings



Cultural spaces


















Facades




Fairgrounds

Specifications (Series luminaires)



 Voltage (V)	24 dcV	 Measures	300x38x83mm
 Dimming	DMX	 Weight	0.78Kg
 IP Tightness index	IP66	 Operating temperature	-30°C ~ +50°C
 IK Impact resistance	IK08	 Surges protection	No
 Body color	9007	 Flux (lm)	280lm
 Diffuser Material	PC	 Electrical isolation	CIII
 Body	AL	 Lifetime	(L70B50>)50.000h
K Colour temperature	RGBW(W:3000)		
 CRI Colour rendering index	>RGBW(W:3000)		

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions



References

	W	ϕ_{LUM}	ϕ/W	
693875	7W	280lm	40lm/W	Yes



485135

MASTER DMX 512 1
UNIVERSE



481687

POWER SUPPLY
150W 24V IP66 PLUG/
IP44



488457

FUENTE DE
ALIMENTACION 60W
24V IP66 CONECTOR



488464

POWER SUPPLY
100W 24V IP66 PLUG/
IP44



529037

MASTER DMX 512 2
UNIVERSOS



571968

FUENTE DE
ALIMENTACION
200W 24V IP67



662932

ADAPT. 15CM NEGRO
CONEC.SMART LINK
A HEMBRA RÁPIDO



701600

BLOQUE CONEXION
T 5P CON
ADAPTADOR




705028

CONECTOR WC
AUTOBLOCANTE
MACHO/HEMBRA 2P




705042

CONECTOR WC
AUTOBLOCANTE
MACHO/HEMBRA 5P



708739

MG 60245 IEC57
(YZW) 2X1+3X0,3
CORTE 1 METRO



715249

MG-XTREM H07 RN-F
2X1 450/750V CORTE
1 METRO