




Applications



Historic buildings



Cultural spaces





Facades







Fairgrounds


Specifications (Series luminaires)



 Voltage (V)	24 dcV
 Dimming	DMX


 Measures	1.000x50x105mm
 Weight	0.0028Kg


 IP Tightness index	IP66
 IK Impact resistance	IK08


 Operating temperature	-30°C ~ +50°C
--	---------------

 Body color	9007
--	------


 Surges protection	No
--	----

 Diffuser Material	PC
---	----


 Body	AL
--	----

 Flux (lm)	2,885lm
--	---------

K Colour temperature	RGBW(W:3000)
------------------------------------	--------------


 Electrical isolation	CIII
---	------

 CRI Colour rendering index	>RGBW(W:3000)
--	---------------

 Lifetime	(L70B50>)50.000h
--	------------------



Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.


Dimensions



References



	W	ϕ_{LUM}	ϕ/W	
693882	72W	2885lm	40lm/W	Yes



485135

MASTER DMX 512 1
UNIVERSE



481687

POWER SUPPLY
150W 24V IP66 PLUG/
IP44



488457

FUENTE DE
ALIMENTACION 60W
24V IP66 CONECTOR



488464

POWER SUPPLY
100W 24V IP66 PLUG/
IP44



529037

MASTER DMX 512 2
UNIVERSOS



571968

FUENTE DE
ALIMENTACION
200W 24V IP67



662932

ADAPT. 15CM NEGRO
CONEC.SMART LINK
A HEMBRA RÁPIDO



701600

BLOQUE CONEXION
T 5P CON
ADAPTADOR




705028

CONECTOR WC
AUTOBLOCANTE
MACHO/HEMBRA 2P




705042

CONECTOR WC
AUTOBLOCANTE
MACHO/HEMBRA 5P



708739

MG 60245 IEC57
(YZW) 2X1+3X0,3
CORTE 1 METRO



715249

MG-XTREM H07 RN-F
2X1 450/750V CORTE
1 METRO