




---

## Applications

---



Historic buildings



Cultural spaces


















Facades



Fairgrounds


## Specifications (Series luminaires)

	<b>Voltage (V)</b>	100-240V
Hz	<b>Frecuency (Hz)</b>	50/60Hz
$\phi$	<b>Power factor (Cos fi)</b>	$\geq 0,9$
	<b>Dimming</b>	No
	<b>IP Tightness index</b>	IP66
	<b>IK Impact resistance</b>	IK08
	<b>Body color</b>	9007
	<b>Diffuser Material</b>	PC
	<b>Body</b>	AL
K	<b>Colour temperature</b>	3000K
	<b>CRI Colour rendering index</b>	>80

	<b>Measures</b>	1.000x38x96mm
	<b>Weight</b>	0.0015Kg
	<b>Operating temperature</b>	-30°C ~ +50°C
	<b>Surges protection</b>	No
	<b>Flux (lm)</b>	3,365lm
	<b>Electrical isolation</b>	CI
	<b>Lifetime</b>	(L70B50>)50.000h


Prilux guarantees a  $\pm 10\%$  tolerance in light flux measurements.

## Dimensions



## References

	W	$\phi_{LUM}$	$\phi/W$	
693905	42W	3365lm	80lm/W	No




---

## 705035

---

CONECTOR WC  
AUTOBLOCANTE  
MACHO/HEMBRA 3P



---

## 715263

---

MG-XTREM H07 RN-F  
3G1 450/750 CORTE 1  
METRO