




---

## Applications

---



Historic buildings



Cultural spaces



Facades
















Fairgrounds



## Specifications (Series luminaires)




 <b>Voltage (V)</b>	110-240 acV
<b>Hz Frecuency (Hz)</b>	50/60Hz
$\phi$ <b>Power factor (Cos fi)</b>	$\geq 0,9$
 <b>Dimming</b>	No
 <b>IP Tightness index</b>	IP66
 <b>IK Impact resistance</b>	IK08
 <b>Body color</b>	9007
 <b>Diffuser Material</b>	PC
 <b>Body</b>	AL
<b>K Colour temperature</b>	4000K
 <b>CRI Colour rendering index</b>	>80

 <b>Measures</b>	1.000x38x96mm
 <b>Operating temperature</b>	-30°C ~ +50°C
 <b>Surges protection</b>	No
$\phi_{LUM}$ <b>Flux (lm)</b>	3,365lm
 <b>Electrical isolation</b>	CI
 <b>Lifetime</b>	(L70B50>)50.000h



Prilux guarantees a  $\pm 10\%$  tolerance in light flux measurements.



## Dimensions



## References



	<b>W</b>	$\phi_{LUM}$	$\phi/W$	
693912	42W	3365lm	80lm/W	No



---

**705035**

---

CONECTOR WC  
AUTOBLOCANTE  
MACHO/HEMBRA 3P

---

**715263**

---

MG-XTREM H07 RN-F  
3G1 450/750 CORTE 1  
METRO