



Specifications (Series luminaires)

	Voltage (V)	V
Hz	Frecuency (Hz)	50/60Hz
	Current (A)	700mA
ϕ	Power factor (Cos fi)	0.96
	LED number	72
	Dimming	No

	IP Tightness index	IP66
	IK Impact resistance	IK10
	Body color	9007T
	Diffuser Material	VT-T 6mm
	Body	AL IAP

K	Colour temperature	4000K
	CRI Colour rendering index	>70
	Optical	VA159X75P
	Higher Hemispheric Flow	max. 0lm

	Measures	540x230x112mm
	Weight	0.004Kg
	Wind Resistance	0,124m2

	Operating temperature	-40°C ~ +50°C
---	------------------------------	---------------

ϕ_{LUM}	Flux (lm)	4,071lm
--------------	------------------	---------

	Electrical isolation	CI
---	-----------------------------	----


	Lifetime	L70B10>100.000h
---	-----------------	-----------------

ϕ/W	Efficacy	151lm/W
----------	-----------------	---------


References

		W_{LED}	W		ϕ	ϕ_{LED}	ϕ_{LUM}	ϕ/W		K
720069		24W	27W	700mA	-1m	-1m	4071lm	151lm/W	72	4000K

Dimensions



Photometry





586566

ADAP KIT. A POST
Ø33MM VERSA-
ARISA ROAD



496636

KIT ADAP. A POSTE
Ø42MM VERSA-
ARISA PRO ROAD



496629

KIT ADAP. A POSTE
Ø50MM VERSA-
ARISA PRO ROAD



501743

ADAP KIT. TO POST
Ø76MM VERSATILE
TECH. RAL9007T



499521

FIJACION BACULO
VERSA Ø76MM
RAL9007T