



Applications



Monuments



Fairgrounds



Facades

















Historic buildings



Cultural spaces

Specifications (Series luminaires)



 Voltage (V)	220-240V	 Measures	233x94x165mm
Hz Frecuency (Hz)	50-60Hz	 Weight	1.2Kg
 Current (A)	max.1400mA	 Operating temperature	-40~+40°C
ϕ Power factor (Cos fi)	Hasta 0,97	 Surges protection	No
 Dimming	DALI	 Electrical isolation	CI
 IP Tightness index	IP67	 Lifetime	L90B10>200.000h
 IK Impact resistance	IK10		
 Body color	9007		
 Body	FE		
 CRI Colour rendering index	>70		




Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions



References



	W		
628495	58,8W	1400mA	Yes
628501	58,8W	1400mA	Yes

Accessories



480307

ACCESS. 3P TANEK
ARCH CONNECTOR

480291

ACCESS. 2P TANEK
ARCH CONNECTOR



628730







480635

ACCES. SUPPORT
BOX TANEK ARQ
REMOTE



628716

CONNECTION KIT
TANEK ARQ NEO
REMOTE 5M



628723

REMOTE 20M







Technologies



Overstorm

Overstorm



OVERSTORM technology is designed for those luminaires that normally face electrically aggressive environments. It provides the product with three spheres of protection: In the outer sphere, an independent surge protector suppresses eventual voltage surges, in the intermediate sphere the drivers are prepared to withstand voltage peaks of up to 6 kV and 10kV. In the nuclear sphere, the protection in the LED module is provided both at its input, for small surges that have not been filtered by the external spheres.

Warning



The RSSY remote installation systems are indivisibly composed of HEXAGON RSSY floodlights connected to a POWER BOX(not included in the luminaire). The POWER BOX must be purchased separately. Check with your local sales representative for the best combination adapted to your installation.