



Specifications (Series luminaires)		
	Electrical isolation	CII
	Voltage (V)	230V
	Frecuency (Hz)	50-60Hz
	Power factor (Cos fi)	Hasta >0,9
	Dimming	No
	IP Tightness index	IP20
	Body color	White
	Diffuser Material	PS
	Colour temperature	3000K-4000K-6500K
	CRI Colour rendering index	>80
	Opening angle	120°
	Measures	220x220x15mm
	Mounting position	Empotrado Techo
	Operating temperature	-5°C ~ +35°C
	Flux (lm)	max. 2450lm
	Lifetime	(L70B50>)35.000h

References



	W	ϕ_{LUM}	K					
671576	6W	510lm	3000K 4000K 6500K	80	White	107X107	220x220x15mm	No
671583	9W	765lm	3000K 4000K 6500K	80	White	135x135	220x220x15mm	No
671590	12W	1200lm	3000K 4000K 6500K	80	White	155X155	220x220x15mm	No
671606	18W	1820lm	3000K 4000K 6500K	80	White	203X203	220x220x15mm	No
671637	18W	1820lm	3000K 4000K 6500K	80	White	-	224x224x32mm	No
671644	24W	2450lm	3000K 4000K 6500K	80	White	-	200x300x200mm	No
671705	6W	510lm	3000K 4000K 6500K	80		107X107	220x220x15mm	No
671712	9W	765lm	3000K 4000K 6500K	80		135x135	220x220x15mm	No
671729	12W	1200lm	3000K 4000K 6500K	80		155X155	220x220x15mm	No
671736	18W	1820lm	3000K 4000K 6500K	80		203X203	220x220x15mm	No
671767	18W	1820lm	3000K 4000K 6500K	80		-	0x0x0mm	No
671774	24W	2450lm	3000K 4000K 6500K	80		-	0x0x0mm	No

Dimensions

Photometry

