




















Specifications (Series luminaires)

| | | |
|---|-----------------------------------|-------------------|
|  | Electrical isolation | CII |
|  | Voltage (V) | 220-240V |
| Hz | Frecuency (Hz) | 50/60Hz |
|  | Power factor (Cos fi) | Hasta $\geq 0,9$ |
|  | Dimming | No |
|  | IP Tightness index | IP20 |
|  | Body color | Black |
|  | Diffuser Material | PC |
|  | Body | AL |
| K | Colour temperature | 2700K-3000K-4000K |
|  | CRI Colour rendering index | >90 |
|  | Opening angle | 20-60 |
|  | Measures | 82x252x158mm |
|  | Mounting position | MONTAJE EN CARRIL |
|  | Inclination | 90° |
|  | Operating temperature | -20°C ~ +40°C |
|  | Flux (lm) | max. 3238lm |
|  | Lifetime | (L70B50>)50.000h |

References

|  | W | ϕ_{LUM} | K |  |  |
|---|-----|--------------|-------|---|---|
| 701747 | 25W | 2339lm | 2700K | White | 82x252x158mm |
| | 30W | 2785lm | 3000K | | |
| | 35W | 3238lm | 4000K | | |
| 701754 | 25W | 2339lm | 2700K | Black | 82x252x158mm |
| | 30W | 2785lm | 3000K | | |
| | 35W | 3238lm | 4000K | | |

Dimensions



Photometry